


SELECTION GUIDE

 MODEL #	TYPE of TOOL	TYPICAL USES	MAX VERTICAL TORQUE		MAX HORZ. TORQUE *		MAX TOOL WEIGHT ^		TOOL HOLDER OPTIONS AVAILABLE	TOOL HOSE ID
			in-lbs	Nm	in-lbs	Nm	Lbs	kg		
PA506	in-line pneumatic	vertical fasteners	550	62	275	31	6	2.7	yes	5/16"
PA506 with IR40 Adapter	to adapt to pistol or right angle holder	horizontal or angled fasteners ^^	N/A	N/A	275	31	6	2.7	purchase PA506 & IR40 & IR tool holder separately	5/16"***
PA506-EL	in-line electric	vertical fasteners	550	62	275	31	5	2.25	yes, UVTH included	none
PA506-OM	in-line pneumatic	overhead mounting vertical fasteners	550	62	275	31	6	2.7	yes	5/16"
PA506-EL-OM	in-line electric	overhead mounting vertical fasteners	550	62	275	31	5	2.25	yes, UVTH included	none
PA806-OM	in-line pneumatic	overhead mounting vertical fasteners	800	90	400	45	6	2.7	yes	3/8"
PA815-OM	in-line pneumatic	overhead mounting vertical fasteners	800	90	400	45	15	6.75	yes	3/8"
PA506-SW	in-line pneumatic	swivel for fasteners on various angles	180	20	N/A	N/A	6	2.7	no	5/16"
PA806	in-line pneumatic	vertical fasteners	800	90	400	45	6	2.7	yes	3/8"
PA815	in-line pneumatic	vertical fasteners	800	90	400	45	15	6.75	yes	3/8"
PA506-DF	in-line, lever-permit pneumatic	self tapping vertical fasteners using 15 lbs of down force	550	62	N/A	N/A	6	2.7	no	5/16"
PA815-DF	in-line, lever-permit pneumatic	self tapping vertical fasteners using 25 lbs of down force	800	90	N/A	N/A	15	6.75	no	3/8"
PAT806-4	special 400 RPM tap motor included	vertical thread tapping up to 9/16" in mild steel	276	31	N/A	N/A	5	2.25	no, ARO50 included	5/16"
PAT806-6	special 600 RPM tap motor included	vertical thread tapping up to 3/8" in mild steel	168	19	N/A	N/A	5	2.25	no, ARO50 included	5/16"
PAT806-4MC	tap motor and auto mist lube included	vertical thread tapping up to 9/16", with mist coolant	276	31	N/A	N/A	5	2.25	no, ARO50 included	5/16"
PAT806-6MC	tap motor and auto mist lube included	vertical thread tapping up to 3/8", with mist coolant	168	19	N/A	N/A	5	2.25	no, ARO50 included	5/16"

* Fasteners driven horizontally -Pistol driver in IR holder or right angle tool in UVTH holder, ect

^ Includes combined weight of bit holders, bits or sockets, & tool holder options

** Braided supply hose with reusable swivels can be supplied with enough length for pistols and other tools at N/C- request when placing order

^^ Use PA806 or PA815 with IR40 for horizontal fasteners needing higher torque and/or tool weight